



# Nexis Click-on 29


125° hinge for standard doors.



- Opening angle 125°
- Soft-close compatible
- Up to 19 mm door thickness
- Self-closing
- 3-dimensional adjustment with suitable mounting plate



## Full overlay Cranking 00




Cup hinge: steel, nickel-plated  
Hinge arm: steel, nickel-plated

Drilling pattern	Item No.	Item No.
48/9	146.329.55.0015	146.329.56.0015
42/11	138.329.73.0015	138.329.74.0015
	PU 250 pieces	PU 250 pieces

Cover caps for cranking 00	Item No.
 *	Steel, nickel-plated, without imprint, Soft-close compatible 514.300.21.0215
 **	Black plastic, without imprint, Soft-close compatible 514.000.22.9762
	PU 1000 pieces

## Half overlay Cranking 08



Cup hinge: steel, nickel-plated  
Hinge arm: steel, nickel-plated

Drilling pattern	Item No.	Item No.
48/9	146.329.55.0815	146.329.56.0815
42/11	138.329.73.0815	138.329.74.0815
	PU 250 pieces	PU 250 pieces

Cover caps for cranking 08	Item No.
 *	Steel, nickel-plated, without imprint, Soft-close compatible 514.300.22.0015
 **	Black plastic, without imprint, Soft-close compatible 514.000.22.9762
	PU 1000 pieces

- \* \*\* on request with individual company logo
- \* \*\* on request with Grass imprint
- \* on request with Grass embossed

PU = packaging unit

Soft-close Click-on	Page 5.8	illuxo Click-on	Page 7.6	Assembly aids	Chapter 10
Tipmatic Click-on	Page 6.8	Click-on mounting plates	Page 2.62 - 2.71	Technical Information	Page 2.74 - 2.77

