


Nexis Click-on 05


95° profiled door hinge for doors up to 30 mm thick.



- Opening angle 95°
- Minimum gap requirements for thick doors
- Soft-close compatible
- Up to 30 mm door thickness
- Self-closing
- 3-dimensional adjustment with suitable mounting plate



Full overlay Cranking 00



Cup hinge: steel, nickel-plated
Hinge arm: steel, nickel-plated

Drilling pattern	Item No.	Item No.
48/9	146.305.53.0015	146.305.54.0015
42/11	138.305.73.0015	138.305.74.0015
	PU 250 pieces	PU 250 pieces

Cover caps for cranking 00



*

Steel, nickel-plated, without imprint, Soft-close compatible


Item No.
514.300.21.0215
514.000.22.9762
PU 1000 pieces



**

Black plastic, without imprint, Soft-close compatible


Half overlay Cranking 08



Cup hinge: steel, nickel-plated
Hinge arm: steel, nickel-plated

Drilling pattern	Item No.	Item No.
48/9	146.305.53.0815	146.305.54.0815
42/11	138.305.73.0815	138.305.74.0815
	PU 250 pieces	PU 250 pieces

Inset Cranking 15



Cup hinge: steel, nickel-plated
Hinge arm: steel, nickel-plated

Drilling pattern	Item No.	Item No.
48/9	146.305.53.1515	146.305.54.1515
42/11	138.305.73.1515	138.305.74.1515
	PU 250 pieces	PU 250 pieces

Cover caps for cranking 08 and 15



*

Steel, nickel-plated, without imprint, Soft-close compatible

Item No.
514.300.22.0015
514.000.22.9762
PU 1000 pieces



**

Black plastic, without imprint, Soft-close compatible

* ** on request with individual company logo

* ** on request with Grass imprint

* on request with Grass embossed

PU = packaging unit

Soft-close Click-on	Page 5.8	illuxo Click-on	Page 7.6	Assembly aids	Chapter 10
Tipmatic Click-on	Page 6.8	Click-on mounting plates	Page 2.62 - 2.71	Technical Information	Page 2.74 - 2.77

